

## LOUNGE ASSEMBLY INSTRUCTION

### CAUTION:

1. Please read these instructions carefully before assembling. Count and organize all parts before you begin.
2. Assemble product on clean soft surface, such as a piece of carpet, so as to prevent the surface paint of parts from scratching off.

PARTS&HARDWARE LIST		
No.	DESCRIPTION	QTY
A	SEAT 122.5*56.5cm	1
B	BACK 66*57cm	1
C	LEG 28*15CM	2
D	ARM(LEFT&RIGHT) 66*48CM	2
E	SUPPORTING STRIP	1
F	LINKING STRIP OF TYRE	1
G	TYRE DIA27	2
H	M8×30 HEADLESS SCREW	8
I	M10×25 HEXAGON SCREW	2
J	M8×40 FLAT HEAD SCREW	2
K	M8×45 FLAT HEAD SCREW	2
L	COPPER CAST	2
M	M8 FLAT WASHER	12
N	BIG FLAT WASHER DIA 3CM	2
O	M8 NUT	8
P	M8 DOMED NUT	4
Q	FEET PAD DIA 2CM	4
R	M8 SPRING WASHER	12
S	BOLT CAP M8	8

### ASSEMBLY:

1. Connect seat (A) to the left or right arms (D) with (H, M, R, and O).
2. Slip (F) on to the arms for both ends, and then connect to seat with (H, M, R and O).
3. Fix legs to seat with (H, M, R, and O).
4. Install (L) the two ends of (F), then slip (G) on and fixed with (I, N).
5. Adjust the installed deck chair to even, which is to adjust the legs, arms to the same place, then tighten screws.
6. Connect (B) & (E) with (J, M, R and P), do not over tighten.
7. Connect seat (A) with back (B) with (K, M, R and P), do not over tighten.
8. Slide all bolt caps onto all exposed screw ends.
9. If not even, adjust foot pads (Q)

**Over tightening can damage aluminum parts**

**PLEASE DO NOT OVER TIGHTEN**

**(Aluminum is soft metal; over tightening may strip thread or break parts)**